


Micro COMBICON Plugs

- Polyamide Insulating Material
- Voltage: 125, Amps: 4, AWG: 28-20
- Spring-Cage Plug
- Suitable for Use in Miniature Modules with a High-Contact Density
- Plug-In Direction Parallel to the Conductor Axis



1881325



Stock No.	Mfr.'s Type	Description	Pin Spacing	No. of Pos.	EACH			
					1-24	25-49	50-99	100-249
70054694	1881325	FK-MC 0.5/2-ST-2.5	2.50 mm	2	2.59	2.32	2.17	1.99
70054695	1881338	FK-MC 0.5/3-ST-2.5	2.50 mm	3	3.45	3.33	3.17	2.92
70054696	1881341	FK-MC 0.5/4-ST-2.5	2.50 mm	4	4.62	4.46	4.23	3.91
70054697	1881354	FK-MC 0.5/5-ST-2.5	2.50 mm	5	5.77	5.57	5.29	4.89
70054698	1881367	FK-MC 0.5/6-ST-2.5	2.50 mm	6	6.34	6.14	5.85	5.68
70054699	1881370	FK-MC 0.5/7-ST-2.5	2.50 mm	7	7.40	7.16	6.83	6.62
70054700	1881383	FK-MC 0.5/8-ST-2.5	2.50 mm	8	8.43	8.16	7.78	7.55
70054701	1881396	FK-MC 0.5/9-ST-2.5	2.50 mm	9	9.50	9.20	8.77	8.51
70054702	1881406	FK-MC 0.5/10-ST-2.5	2.50 mm	10	10.55	10.22	9.74	9.45
70054703	1881419	FK-MC 0.5/11-ST-2.5	2.50 mm	11	11.61	11.24	10.72	10.40
70054704	1881422	FK-MC 0.5/12-ST-2.5	2.50 mm	12	12.67	12.26	11.69	11.34

Mini COMBICON Plugs

- Polyamide Insulating Material
- Voltage: 125, Amps: 8, AWG: 30-14
- Very Economical and Low Height
- Plug-In Direction Parallel to the Conductor Axis



1840366



Stock No.	Mfr.'s Type	Description	Pin Spacing	No. of Pos.	EACH			
					1-24	25-49	50-99	100-249
70054705	1840366	MC 1.5/2-ST-3.5	3.50 mm	2	2.02	1.86	1.59	1.49
70054706	1840379	MC 1.5/3-ST-3.5	3.50 mm	3	3.06	2.79	2.40	2.21
70054707	1840382	MC 1.5/4-ST-3.5	3.50 mm	4	4.00	3.68	3.15	2.93
70054708	1840395	MC 1.5/5-ST-3.5	3.50 mm	5	5.12	4.71	4.02	3.73
70054709	1840405	MC 1.5/6-ST-3.5	3.50 mm	6	5.64	5.44	5.17	4.77
70054710	1840418	MC 1.5/7-ST-3.5	3.50 mm	7	6.60	6.37	6.05	5.59
70054711	1840421	MC 1.5/8-ST-3.5	3.50 mm	8	6.87	6.64	6.34	6.15
70054712	1840434	MC 1.5/9-ST-3.5	3.50 mm	9	7.77	7.52	7.17	6.96
70054713	1840447	MC 1.5/10-ST-3.5	3.50 mm	10	8.65	8.37	7.99	7.75
70054714	1840450	MC 1.5/11-ST-3.5	3.50 mm	11	9.51	9.20	8.77	8.51
70054715	1840463	MC 1.5/12-ST-3.5	3.50 mm	12	10.32	9.98	9.53	9.24
70054716	1840476	MC 1.5/13-ST-3.5	3.50 mm	13	11.22	10.86	10.35	10.05
70054717	1840489	MC 1.5/14-ST-3.5	3.50 mm	14	10.36	—	—	—
70054718	1840492	MC 1.5/15-ST-3.5	3.50 mm	15	11.09	—	—	—
70054719	1840502	MC 1.5/16-ST-3.5	3.50 mm	16	13.81	13.36	12.75	12.36
70054750	1830578	MC 1.5/2-ST-3.81	3.81 mm	2	1.80	1.65	1.43	1.34
70054751	1830581	MC 1.5/3-ST-3.81	3.81 mm	3	2.65	2.51	2.14	1.98
70054752	1830594	MC 1.5/4-ST-3.81	3.81 mm	4	3.74	3.41	2.94	2.73
70054753	1830604	MC 1.5/5-ST-3.81	3.81 mm	5	4.58	4.15	3.62	3.35
70054754	1830617	MC 1.5/6-ST-3.81	3.81 mm	6	5.61	5.07	4.71	4.35
70054755	1830620	MC 1.5/7-ST-3.81	3.81 mm	7	6.65	5.97	5.53	5.11
70054756	1830633	MC 1.5/8-ST-3.81	3.81 mm	8	7.26	6.73	5.87	5.45
70054757	1830646	MC 1.5/9-ST-3.81	3.81 mm	9	8.51	7.93	7.10	6.56
70054758	1830659	MC 1.5/10-ST-3.81	3.81 mm	10	9.41	8.46	7.84	7.23
70054759	1830662	MC 1.5/11-ST-3.81	3.81 mm	11	10.39	9.69	8.66	7.99
70054760	1830675	MC 1.5/12-ST-3.81	3.81 mm	12	11.32	10.18	9.43	8.71
70054761	1830688	MC 1.5/13-ST-3.81	3.81 mm	13	12.19	11.29	10.16	9.38
70054762	1830691	MC 1.5/14-ST-3.81	3.81 mm	14	13.22	11.88	11.02	10.18
70054763	1830701	MC 1.5/15-ST-3.81	3.81 mm	15	14.17	12.73	11.81	10.90
70054764	1830714	MC 1.5/16-ST-3.81	3.81 mm	16	15.08	13.57	12.59	11.61

COMBICON Vertical Plugs

- Polyamide Insulating Material
- Voltage: 300, Amps: 10, AWG: 30-12
- Vertical Plugs Can Be Placed Close to the Neighboring Walls and Removed without Compressing the Connected Conductors



1737709



1737819



Stock No.	Mfr.'s Type	Description	Pin Spacing	No. of Pos.	EACH			
					1-24	25-49	50-99	100-249
70054894	1737709	GMVSTBR 2.5/2-ST	7.50 mm	2	3.16	2.93	2.62	2.41
70054895	1737712	GMVSTBR 2.5/3-ST	7.50 mm	3	4.70	4.23	3.93	3.64
70054896	1737725	GMVSTBR 2.5/4-ST	7.50 mm	4	6.17	5.76	5.15	4.76
70054897	1737738	GMVSTBR 2.5/5-ST	7.50 mm	5	5.50	—	—	—
70054898	1737741	GMVSTBR 2.5/6-ST	7.50 mm	6	9.24	8.61	7.72	7.11
70054899	1737754	GMVSTBR 2.5/7-ST	7.50 mm	7	7.71	—	—	—
70054900	1737767	GMVSTBR 2.5/8-ST	7.50 mm	8	8.79	—	—	—
70054901	1737770	GMVSTBR 2.5/9-ST	7.50 mm	9	14.03	13.07	11.69	10.79
70054902	1737783	GMVSTBR 2.5/10-ST	7.50 mm	10	15.56	14.53	12.98	11.98
70054903	1737796	GMVSTBR 2.5/11-ST	7.50 mm	11	17.12	15.97	14.26	13.16
70054904	1737806	GMVSTBR 2.5/12-ST	7.50 mm	12	13.20	—	—	—

- Plug-In Direction Vertical to the Conductor Axis

- Connection Point Facing the Rippled Wall of the Header

Stock No.	Mfr.'s Type	Description	Pin Spacing	No. of Pos.	EACH			
					1-24	25-49	50-99	100-249
70054905	1737819	GMVSTBW 2.5/2-ST	7.50 mm	2	3.16	2.93	2.62	2.41
70054906	1737822	GMVSTBW 2.5/3-ST	7.50 mm	3	4.71	4.40	3.92	3.64
70054907	1737835	GMVSTBW 2.5/4-ST	7.50 mm	4	6.17	5.76	5.15	4.76
70054908	1737848	GMVSTBW 2.5/5-ST	7.50 mm	5	5.50	—	—	—
70054909	1737851	GMVSTBW 2.5/6-ST	7.50 mm	6	9.23	9.05	7.72	7.12
70054910	1737864	GMVSTBW 2.5/7-ST	7.50 mm	7	10.92	10.17	9.11	8.39
70054911	1737877	GMVSTBW 2.5/8-ST	7.50 mm	8	8.79	—	—	—
70054912	1737880	GMVSTBW 2.5/9-ST	7.50 mm	9	14.03	13.07	11.69	10.79
70054913	1737893	GMVSTBW 2.5/10-ST	7.50 mm	10	15.56	14.53	12.98	11.98
70054914	1737903	GMVSTBW 2.5/11-ST	7.50 mm	11	17.12	15.97	14.26	13.16
70054915	1737916	GMVSTBW 2.5/12-ST	7.50 mm	12	18.50	17.27	15.42	14.23

Mini COMBICON Vertical Plugs

- Polyamide Insulating Material
- Voltage: 300, Amps: 8, AWG: 30-14
- Plug-In Direction Vertical to the Conductor Axis



1863152



1862852



- Can Be Placed Close to Neighboring Walls and Removed from Above without Compressing the Connected Lines

Stock No.	Mfr.'s Type	Description	Pin Spacing	No. of Pos.	EACH			
					1-24	25-49	50-99	100-249
70054720	1863152	MCVR 1.5/2-ST-3.5	3.50 mm	2	2.07	1.86	1.74	1.61
70054721	1863165	MCVR 1.5/3-ST-3.5	3.50 mm	3	3.07	2.87	2.57	2.36
70054722	1863178	MCVR 1.5/4-ST-3.5	3.50 mm	4	4.11	3.71	3.43	3.17
70054723	1863181	MCVR 1.5/5-ST-3.5	3.50 mm	5	5.14	4.64	4.31	4.00
70054724	1863194	MCVR 1.5/6-ST-3.5	3.50 mm	6	6.14	5.74	5.12	4.73
70054725	1863204	MCVR 1.5/7-ST-3.5	3.50 mm	7	7.11	6.65	5.94	5.49
70054726	1863217	MCVR 1.5/8-ST-3.5	3.50 mm	8	8.21	7.65	6.84	6.32
70054727	1863220	MCVR 1.5/9-ST-3.5	3.50 mm	9	6.52	—	—	—
70054728	1863233	MCVR 1.5/10-ST-3.5	3.50 mm	10	10.24	9.57	8.54	7.88
70054729	1863246	MCVR 1.5/11-ST-3.5	3.50 mm	11	11.31	10.54	9.42	8.71
70054730	1863259	MCVR 1.5/12-ST-3.5	3.50 mm	12	12.34	11.11	10.29	9.51
70054731	1863262	MCVR 1.5/13-ST-3.5	3.50 mm	13	9.42	—	—	—
70054732	1863275	MCVR 1.5/14-ST-3.5	3.50 mm	14	14.39	13.42	11.99	11.07
70054733	1863288	MCVR 1.5/15-ST-3.5	3.50 mm	15	10.88	—	—	—
70054734	1863291	MCVR 1.5/16-ST-3.5	3.50 mm	16	16.43	15.32	13.70	12.64
70054765	1827127	MCVR 1.5/2-ST-3.81	3.81 mm	2	1.96	1.83	1.54	1.45
70054766	1827130	MCVR 1.5/3-ST-3.81	3.81 mm	3	3.05	2.76	2.56	2.34
70054767	1827143	MCVR 1.5/4-ST-3.81	3.81 mm	4	4.08	3.65	3.41	3.14
70054768	1827156	MCVR 1.5/5-ST-3.81	3.81 mm	5	5.08	4.59	4.25	3.94
70054769	1827169	MCVR 1.5/6-ST-3.81	3.81 mm	6	6.10	5.69	5.08	4.69
70054770	1827172	MCVR 1.5/7-ST-3.81	3.81 mm	7	7.12	6.41	5.93	5.49
70054771	1827185	MCVR 1.5/8-ST-3.81	3.81 mm	8	8.14	7.33	6.79	6.27
70054772	1827198	MCVR 1.5/9-ST-3.81	3.81 mm	9	9.18	8.55	7.65	7.04
70054773	1827208	MCVR 1.5/10-ST-3.81	3.81 mm	10	10.17	9.14	8.49	7.83
70054774	1827211	MCVR 1.5/11-ST-3.81	3.81 mm	11	11.20	10.45	9.34	8.61
70054775	1827224	MCVR 1.5/12-ST-3.81	3.81 mm	12	12.24	11.40	10.19	9.41
70054776	1827237	MCVR 1.5/13-ST-3.81	3.81 mm	13	13.21	12.32	11.02	10.17
70054777	1827240	MCVR 1.5/14-ST-3.81	3.81 mm	14	10.07	—	—	—
70054778	1827253	MCVR 1.5/15-ST-3.81	3.81 mm	15	15.27	14.25	12.75	11.75
70054779	1827266	MCVR 1.5/16-ST-3.81	3.81 mm	16	16.29	14.64	13.58	12.53